

Data Record Sheet for TSP Monitoring

Monitoring Location		
Details of Location		
Sampler Identification		
Date & Time of Sampling		
Elapsed-time Meter Reading	Start (min.)	
	Stop (min.)	
Total Sampling Time (min.)		
Weather Conditions		Sunny / Fine / Cloudy / Rainy
Site Conditions		
Initial Flow Rate, Qsi	Pi (mmHg)	
	Ti (°C)	
	Hi (in.)	
	Qsi (Std. m ³)	
Final Flow Rate, Qsf	Pf (mmHg)	
	Tf (°C)	
	Hf (in.)	
	Qsf (Std. m ³)	
Average Flow Rate (Std. m ³)		
Total Volume (Std. m ³)		
Filter Paper Identification No.		
Initial Wt. of Filter Paper (g)		
Final Wt. of Filter Paper (g)		
Measured TSP Level (µg/m ³)		
Other Dust Emission Source(s) Observed		
Remarks /Other Observations		

Name & Designation

Signature

Date

Field Operator:

Laboratory Staff:

Checked by:

Construction Noise Monitoring Field Record Sheet

Monitoring Location		
Description of Location		
Date of Monitoring		
Weather Conditions		Sunny / Fine / Cloudy / Rainy
Wind Strength (m/s)		
Measurement Start Time (hh:mm)		
Measurement Time Length (min.)		
Noise Meter Model/Identification		
Calibrator Model/Identification		
Measurement Results	L ₉₀ (dB(A))	
	L ₁₀ (dB(A))	
	L _{eq} (dB(A))	
	Type of Measurement	Free-field / Facade
Major Construction Noise Source(s) During Monitoring		
Other Noise Source(s) During Monitoring		
Remarks / Other Observations		

Name & Designation

Signature

Date

Recorded by:

Checked by:

Water Quality Monitoring Data Record Sheet

Location		Surface	Middle	Bottom
Monitoring Station				
Date				
Weather Conditions		Sunny / Fine / Cloudy / Rainy		
Sea Conditions		Calm / Moderate / Rough		
Tide Mode		High Tide / Low Tide		
Start Time	(hh:mm)			
Water Depth	(m)			
pH				
Temperature	(oC)			
Salinity	(ppt)			
Turbidity	(NTU)			
Sample Identification				
SS	(mg/l)			
DO	(mg/l)			
DO Saturation (%)				
Observed Construction Activities	<100m from location			
	>100m from location			
Other Observations				

Name & Designation

Signature

Date

Recorded by:

Checked by:

Note:

- The SS results are to be entered once they are available from the laboratory.
- In-situ measurements shall be deployed at the designated location for 2 times. The difference between the two consecutive measurements of DO or turbidity parameters shall be within the range of 25%. If the difference is larger than 25%, the measurement shall be carried out again until the two consecutive readings agree to within 25%.